



### Componentes



#### 833-TA-15

Descrip. Triángulo 15  
UDS/CAJA Unitario



#### 833-R2500

Descrip. Rail 2.500 mm  
UDS/CAJA 8



#### 833-TSU-01

Descrip. Grapa triángulo  
UDS/CAJA 125



#### 833-U-01

Descrip. Unión Barra  
UDS/CAJA 70



#### 833-GF

Descrip. Grapa final  
UDS/CAJA 125



#### 833-GI

Descrip. Grapa intermedia  
UDS/CAJA 125

### \*\* Materiales para x módulos 1 fila

	2 Módulos	3 Módulos	4 Módulos	5 Módulos	6 Módulos
833-TA-15	2	3	4	4	5
833-R2500	2	3	4	5	6
833-GI	2	4	6	8	10
833-U-01	0	2	2	4	4
833-TSU-01	6	8	8	8	10
833-GF	4	4	4	4	4

### Especificaciones

Módulo	HASTA 2.090 x 1.040 (para medidas superiores consultar)
Superficie de anclaje	Losa de hormigón, correas metálicas o lastrada
Materiales	Perfilería: Aluminio EN AW 6005A.T6 Tornillería: Acero inoxidable A2-70
Espesor del panel	De 28 a 35 mm
Inclinación	Regulable de 15° a 30°
Peso por módulo	1.84kg /Módulo
Viento	Hasta 120 km/h
Disposición de módulos	Vertical

### Par de apriete

Tornillo Presor	7 Nm
Tornillo M8 Hexagonal	20 Nm
Tornillo M10 Hexagonal	40 Nm

Marcado  
ES19/86524



web

